

FOCO TWO 1200 SLIM

BIO-30-103

With Foco Two 1200 Slim you get an elegant tunnel bioethanol fireplace designed for installation in walls with limited depth. At just 20 cm deep, this fireplace is ideal for thin walls and partitions. It features two open sides, allowing for a view of the flames from both sides of the room. Equipped with an adjustable Superior 1000 bioethanol burner with a 5-liter capacity, the Foco Two Slim offers up to 6 hours of burn time. Its powder-coated stainless steel and tempered glass ensure a timeless design and stable flame.

TECHNICAL SPECIFICATIONS

Burner - Features

| | |
|----------------------|-------------------|
| Burn time | 6 hours |
| Burner type | 5 Litre Superior |
| Flame length | 76 cm |
| Minimum room size | 90 m ³ |
| Requires electricity | No |
| Adjustable flame | Yes |
| Control | Manual |
| Capacity | 5 Litres |
| Heat output (max) | 6,5 kW |
| Remote control | No |
| Usage | 0.87 L/h |

Type

| | |
|-----------------------------|---|
| Flue/chimney | Not Required |
| Recommended air change rate | 1 |
| Producttype | See-through Built-in Bioethanol Fireplace |
| Brand | Foco |
| Fuel | Bioethanol |
| Use | Indoor |
| Warranty | 2 years |

Appearance

| | |
|-----------------|-------|
| Materials | Steel |
| Steel thickness | 4 mm |
| Colour | Black |
| Glas included | Yes |

Size

| | |
|--------------|--------|
| Length/Width | 120 cm |
| Height | 50 cm |
| Depth | 20 cm |
| Weight | 25 kg |



Superior Manual

